

Raychem NRG-TEMP TIMER THERMOSTAT



DESCRIPTION

Digital timer thermostat for floor sensing or/and room sensing applications including min. and max. floor temperature limitation function.

PRODUCT PROPERTIES

Automatic sensing of sensor mode (floor or room)

Manual ON/OFF by 2-pole main power switch

Big display with blue backlight

Built-in timer function

4 operation modes

- Standard mode (Comfort)
- 2 editable pre-programmes (EcoHome, EcoOffice)
- Summer mode (off-mode)

Daily editable in time blocks of 30 minutes

Adaptive function in order to reach desired temperature at desired time

Booster function for fast heat-up (+5°C for max 2 hours)

Read-out of actual floor sensor temperature

Monitoring of floor or room sensor. In the event of failure of an active sensor, the underfloor heating system is switched off.

Possibility to lock the settings e.g. public buildings

OPERATION SENSOR MODE



Room sensing only

Floor sensing only

Room sensing with min./max. floor temperature limitation e.g. for wooden floors

NRG-TEMP TIMER THERMOSTAT

TECHNICAL DATA



Supply voltage	230 VAC +10%, -15%, 50/60 Hz
Relay output	Heating cable 230 V, max 13 A
Temperature range floor sensor	+5°C to +35°C
Temperature range room sensor	+5°C to +40°
Limitation of range	Low +5°C/ high +35°C
Ambient temperature-operation	0°C to +40°C
Ambient temperature-transport	-20°C to +50°C
Accuracy-floor/room sensor	+/- 0,5°C
Switching hysteresis	0,5°C with floor sensor
Control modes	Floor or room sensing or room sensing with limiter
Clock function	2 pre-programmes : EcoHome, EcoOffice; editable in blocks of 30 min; daily programmable
Back-up for set values	Non-volatile memory
Back-up for time and date	24 hrs
Protection class	IP21
Terminals	Max. 2,5 mm ²
Floor sensor	NTC, 10K / 25°C with 3 m cable
Max length of floor sensor	10w0 m, 2 x 1,5 mm ² (230 VAC cable)
Diameter sensor cable	4 mm
Diameter sensor tip	6 mm, length 32 mm
Dimensions with frame	H 82 x W 82 x D 57 mm
Color	Polar white RAL 9010
Approvals	Semko, VDE, EuBac

SYSTEM INFORMATION

Raychem underfloor heating thermostats are used with

- T2QuickNet mats 90 W/m² and 160 W/m²
- T2Red – Self-regulating heating cable
- T2Blue 10 W/m² and T2Blue 20 W/m² heating cables


COMPATIBILITY WITH WALL BOXES

An extra square front plate for square frames is provided as a standard.


Switch manufacturer	Light switch product range
Busch + Jäger	Reflex SI, Jussi
Eljo	Trend
Elko	RS, L571
Gira	ST55 Standard, E2
Jung	AS
Merten	M-Plan, M-Smart, M-Arc, Atelier, M-Antik, Thermo, M-STAR

WIRING DIAGRAM

Direct, connection – e.g. single heating circuit



Connection via contactor – e.g. 3 heating circuits



K1: contactor with integral suppression device

⚠ Do not use contactor without interference filter.

ORDERING INFORMATION

R-TC-NRG	1244-002513
----------	-------------

ACCESSORIES

Silver-R-TC silver coloured front parts	1244-010130
Sensor-N10K spare floor sensor	1244-002952
Silver Raychem TC-NRG-Squared	1244-010132
Adapter UK wall box	1244-010134



WWW.THERMAL.PENTAIR.COM

**Hong Kong & Macao Master Distributor
CAS Systems Limited**

Tel: +852 2682 8022
Email: info@RaychemFloorHeating.hk
Website: www.RaychemFloorHeating.hk

All Pentair trademarks and logos are owned by Pentair. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2013 Pentair. All Rights Reserved.